


CHOOSE FROM OUR SYSTEM MOBILE FENCE

WE WILL ADVISE AND PREPARE YOUR SYSTEM
MOBILE FENCE FOR YOUR PLOT,
CONSTRUCTION AND CULTURAL OR SPORTING EVENTS.
ALL OUR ASSORTMENT CAN BE CUSTOMIZED
ACCORDING TO YOUR REQUIREMENTS.



FLEXPLOTY



FLEXWORK



Pipe construction with mesh paneling. Multiple uses, such as fencing of construction sites, land and property. Simple handling and long service life.

Dimension	3 455 mm x 2 000 mm
Weight	11 kg
Spacing width	260 mm x width: 100 mm
The thickness of the filler wire is	2,3 x 3,3 mm
Vertical tube dia	40 mm
Horizontal tube dia	25 mm
Edging hot-dip galvanized	

FLEXGATE

It is used for better access to the fenced area. Simple handling and installation. Necessary part is a hinge and a nylon wheel.

Dimensions	1 190 mm x 2 000 mm
Weight	7,7 kg
Spacing width	260 mm x width: 100 mm
The thickness of the filler wire is	3,3 mm
Vertical tube dia.	40 mm
Horizontal tube dia.	30 mm
Edging hot-dip galvanized	



FLEXMINI



Pipe construction with mesh filling. Multiple uses such as fencing of construction sites, excavations, for less height, even easier handling.

Dimensions	3 455 mm x 1 200 mm
Weight	11,6 kg
Spacing width	260mm x width: 100mm
The thickness of the filler wire is	3,3 mm
Vertical tube dia.	40 mm
Horizontal tube dia.	30 mm
Edging hot-dip galvanized	

FLEXPANEL

Pipe construction with high-quality hot dip galvanized sheet metal. High stability, opacity And appearance, make FLEXPANEL a very popular fence. We produce in two dimensions.

Dimensions	2 355 mm x 2 000 mm
Weight	26,1 kg
Filling of the structure	hot-dip galvanized sheet
The thickness of the filler plate is	0,5 mm
Vertical tube dia.	40 mm
Edging hot-dip galvanized	



FLEXBAR

Made of all-threaded frame and tubes. We use in construction, cultural and sports action. Very simple handling and transport.

Dimensions	2 513 mm x 1 100 mm
Weight	10,8 kg
Spacing width	260mm x width: 100mm
Vertical pipes	18 pcs
Edging hot-dip galvanized	



CONCRETE FOOT

Is made of high quality concrete mixture is a component of mobile fence system. With holes for sliding fence panels, it creates very flexible possibilities for mobile mounting fence.

Material: Concrete mixture, weight: 30 Kg.

CLAMP

The clamp is made of galvanized material and serves as a reinforcement in the top of the fencing. Serves to connect and create greater fencing stabilization.

The FLEXPANEL product line is used to fasten struts. Installation and disassembly is very Simple using the key.



WHEEL

Wheel for gates and gates, castors made of nylon and very resistant to mechanical use.

Simple mounting on a fence or gable construction makes it a great helper At entrances and entrances into the fenced area.

Material: Nylon, weight: 0.85 Kg.

HINGE

The hinge is part of every gate and gate of the mobile fence system. He is guarded screw for stable mounting and anti-theft protection.

It is made of quality metallurgical material.

Material: Heat-zinc, weight: 1.35 Kg.



BRACE

The braces for increased stability are also hot-dip galvanized and therefore very weather-resistant effects. It is used to increase the stability of the fencing. We use the clutch in the top to mount it fence sections and a concrete foot at the bottom. The strut is supplied with an anchor, by which the strut is anchored.

Material: Heat-zinc, weight: 1.8kg.

CONTACT

Tupolevova 465, 199 00 Praha 9
Czech Republic

Warehouse with dispensary
SEMTÍN - areál SK-EKO Kovošrot
Pardubice 53301

Tel .: +420 733 318 152 - technical consultancy

Tel .: +420 608 756 515

E-mail: obchod@flexploty.cz

Web: www.flexploty.cz

Seller: www.stavebniploty.cz

